



MODEL	A	B	C	D	DEPTH
MK	4.5	2.75	.625	1.375	3

NOTE: FASTENERS NOT SHOWN ALL DIMENSIONS IN INCHES.

ENTRY DEVICE - KEYSWITCH – MK

Features

- 12/24 VDC bi-color LED
- 5 amp rated SPDT plunger switch
- Accepts any brand 1-1/4" or 1-1/8" mortise cylinder
- Additional switch position allows for a second plunger switch
- UL Listed

Operating Temperature
0 to 43C [32 to 110F]

Option

- **A** – Alternate
- **2** – DPDT
- **N** – Narrow Stile



ENTRY DEVICE - KEYSWITCH – MK (cont'd)

How to Order

<u>Part #</u>	<u>Description</u>
MK	Mortise Keyswitch Momentary Single Gang
MKA	Mortise Keyswitch Alternate Single Gang
MK2	Mortise Keyswitch Momentary DPDT Single Gang
MKA2	Mortise Keyswitch Alternate DPDT Single Gang
MKS	Additional Switch Momentary for MK Series
MKSA	Additional Switch Alternate for MK Series
MKS2	Additional Switch Momentary DPDT for MK Series
MKSA2	Additional Switch Alternate DPDT for MK Series
MKN	Mortise Keyswitch Momentary Narrow Stile
MKAN	Mortise Keyswitch Alternate Narrow Stile
MKN2	Mortise Keyswitch Momentary DPDT Narrow Stile
MKAN2	Mortise Keyswitch Alternate DPDT Narrow Stile

Architectural Specifications

- A. The Keyswitch shall be produced by an ISO 9001 certified manufacturer.
- B. The Keyswitch shall be furnished on a Stainless Steel - 630/US32D single gang face plate with a 12/24 VDC bi-color LED
- C. The Keyswitch shall have a 5AMP rated SPDT plunger switch and an integral backing bracket that shall permit integration with any 1.25" or 1.125" mortise cylinder (by others).
- D. Momentarily turning the key shall change the state of the contacts.
- E. An additional switch position on the backing bracket shall be available so another switch may be activated by turning the key in the other direction.